

# High performance, intuitive usability, versatile finishing

The imageRUNNER ADVANCE 8500 Series delivers high performance and quality black-and-white output for high volume office environments and CRDs. These intelligent systems enhance productivity with versatile finishing options while maintaining an intuitive user experience.

Print up to 105ppm in black-and-white  
Scan up to 240/220 ipm (300 dpi) (B/W, Colour, duplex)  
Print up to SRA3  
7,700 maximum paper capacity



## Workflow Efficiency

- An intuitive user interface with a large, responsive colour touchscreen makes carrying out tasks easy.
- Scalable support for mobile and flexible work styles can increase efficiency by allowing workers to capture or print documents and access certain cloud applications on the go.
- Advanced Personalisation enables a unique, personal experience across a fleet, creating a customized user experience tailored to meet each user's workflow needs.
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint files through a single-pass duplexing document feeder that holds up to 300 originals.
- Create professional-looking reports, booklets, newsletters, manuals, proposals, and contracts with flexible finishing options such as professional punching, folding, document insertion, and booklet-making.
- The optional imagePASS print controller, an ideal choice for busy operations, provides robust processing capabilities, variable data printing (VDP), and a print production workflow.

## Cost Management

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimizing downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralized fleet management can help simplify IT management of devices and entire fleets.

## Security

- Control who has access to the device with authentication by using the standard Universal Login Manager application.
- Help prevent unauthorized distribution of sensitive information with an array of standard and optional document security features.
- Help ensure information privacy and security across your entire network with IPsec, port filtering capabilities, and SSL technology.

## Device and Fleet Management Efficiency

- The ability to pre-configure devices makes installation easy and fleet management is simplified with the capability to synchronize settings across multiple devices.
- Canon's device management tools give you a centralized point of control across your entire fleet, including the ability to check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers.
- Standard Genuine Adobe PostScript and PCL support integration with enterprise applications and legacy systems to help streamline business processes.

## Reliability

- Canon's signature reliability and engine technologies provide reliable high quality output to meet the needs of busy departments and Central Reprographics Departments (CRDs)/In-plant Printers.
- State-of-the-art imaging technologies and toner allow for consistently striking images in rich black-and-white tones and 1,200 dpi print resolution.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished, intuitive user maintenance videos, the ability to replace toner on the fly, and automatic job re-routing (with optional solutions).

## Sustainability

- Fusing technologies, pO toner, and innovative sleep mode features help lower overall energy consumption.
- Help minimize waste with default 2-sided printing, secure printing, and the ability to hold print jobs, preview them and change print settings at the device, helping to achieve the results you want the first time.
- Incorporates sustainable design, with the use of recycled materials and bio-based plastic, and a focus on minimizing environmental impact.
- ENERGY STAR qualified and rated EPEAT Silver.



# CONFIGURATION

## iR-ADV 8585



**BOOKLET FINISHER-X1**

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 5 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1) and booklet trimming (Inner Booklet Trimmer-A1)



**STAPLE FINISHER-X1**

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1)



**PAPER FOLDING UNIT-J1**

- Z-fold, C-fold, Half-fold, Accordion Z-fold, Double-parallel Fold



**MULTI FUNCTION PROFESSIONAL PUNCHER-A1**

- Supports various die sets
- Up to 256 gsm
- Supports A3, A4, A4R
- 100,000 sheet punch tray capacity
- Enhanced die durability



**DOCUMENT INSERTION UNIT-J1**

- Insert preprinted sheets
- Up to A3
- Two trays
- 400-sheet total capacity



**BOOKLET FINISHER-V1 (iR-ADV 8585 only)**

- 3-tray, 3,500 -sheet capacity
- Corner and double stapling up to 65 sheets (90gsm)
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Eco Stapling and Staple On Demand
- Supports optional 2/4 and 4 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1



**STAPLE FINISHER-V1 (iR-ADV 8585 only)**

- 3-tray, 3,500 -sheet capacity
- Corner and double stapling up to 65 sheets (90gsm)
- Supports Eco Stapling and Staple On Demand
- Supports optional 2/4 and 4 hole inner Puncher - 2/4 Hole Puncher Unit-A1 and 4 Hole Puncher Unit-A1

**MFP MODEL**




**PAPER DECK UNIT-E1**

- 3,500-sheet capacity
- Supports A4



**POD DECK LITE-C1**

- 3,500-sheet capacity
- 52 to 256 gsm
- Supports up to SRA3
- User adjustable

**imagePASS-Y1**

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalized printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



## iR-ADV 8595/8505



**BOOKLET TRIMMER-D1**

- \*Require BOOKLET FINISHER-W1 PRO



**BOOKLET FINISHER-W1 PRO**

- 2-tray, 5,000-sheet capacity
- Corner and double stapling up to 100 sheets
- Booklet-making up to 25 sheets and saddle-folding up to 5 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BT1 and BG1) and optional booklet trimming (Booklet Trimmer-D1)
- Precise output stacking alignment
- Enhanced durability for high volumes



**STAPLE FINISHER-W1 PRO**

- 2-tray, 5,000-sheet capacity
- Corner and double stapling up to 100 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BT1 and BG1)
- Precise output stacking alignment
- Enhanced durability for high volumes



**BOOKLET FINISHER-X1**

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 5 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1) and booklet trimming (Inner Booklet Trimmer-A1)



**STAPLE FINISHER-X1**

- 3-tray, 4,250-sheet capacity
- Corner and double stapling up to 100 sheets
- Supports optional internal 2/4 and 4-hole puncher (Puncher Unit-BG1 and BH1)



**DOCUMENT INSERTION UNIT-J1**

- Insert preprinted sheets
- Up to A3
- Two trays
- 400-sheet total capacity



**MULTI FUNCTION PROFESSIONAL PUNCHER-A1**

- Supports various die sets
- Up to 256 gsm
- Supports A3, A4, A4R
- 100,000 sheet punch tray capacity
- Enhanced die durability



**PAPER FOLDING UNIT-J1**

- Z-fold, C-fold, Half-fold, Accordion Z-fold, Double-parallel Fold

**MFP MODEL**




**PAPER DECK UNIT-E1**

- 3,500-sheet capacity
- Supports A4



**POD DECK LITE-C1**

- 3,500-sheet capacity
- 52 to 256 gsm
- Supports up to SRA3
- User adjustable

**imagePASS-Y1**

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalized printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules




INNER TRIMMER



INNER PUNCHERS

Please refer to the PAD and online configurator for the accessory attachment relationships and the complete accessory list

## MAIN UNIT

### Machine type

Monochrome Laser Multifunctional Printer

### Core functions

Print, Copy, Scan, Send, Store and Optional Fax

### Processor Speed

Canon Dual Custom Processor (Shared)

### Control Panel

iR-ADV 8585, 8595, 8505: 10.4 inch TFT LCD SVGA  
Color Touchpanel

### Memory

Standard: 3.0GB RAM

### Hard Disk Drive

Standard: 250GB

Maximum: 1TB

### Interface Connection

Network Standard: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)  
Optional: NFC  
Others Standard: USB 2.0 x2 (Host), USB 3.0 x  
1 (Host), USB 2.0 x1 (Device)  
Optional: Serial Interface, Copy Control  
Interface

### Paper Input (Standard)

1,500 sheets x 2 paper cassettes + 550 sheets cassettes  
x 2 cassettes (80gsm)  
100 sheets Multi-purpose tray (80gsm)

### Paper Input (Option)

Additional 3,500 sheets (80gsm)  
(POD DECK LITE-C1 or PAPER DECK UNIT-E1)

### Maximum Paper Input Capacity

7,700 sheets (80gsm)

### Paper Output Capacity

With External Finishers: Max. 5,000 sheets (A4)

### Finishing capabilities

With additional finishing options:

Staple, saddle stitch, eco-staple, manual staple, 2 or 4  
hole punch, professional punching, insertion, folding,  
booklet trimming

### Supported media types

Upper Left/Right Cassettes(1/2):

Thin paper, Plain paper, Recycled paper, Colour paper,  
Heavy paper, Pre-punched paper, Letterhead, Bond paper  
Lower Cassettes (3/4):

Thin paper, Plain paper, Recycled paper, Colour  
paper, Heavy paper, Pre-punched paper, Letterhead,  
Bond paper, Tab paper\*

\*Tab paper can be fed from both cassette 3 & 4 when the  
optional TAB FEEDING ATTACHMENT KIT-B1 is installed.

Multi-purpose tray:

Thin paper, Plain paper, Recycled paper, Colour paper,  
Heavy paper, Pre-punched paper, Bond, Transparency,  
Labels, Letterhead, Clear Film, Tab paper, Tracing\*<sup>1</sup>

POD DECK LITE-C1:

Thin paper, Plain paper, Recycled paper, Colour  
paper, Heavy paper, Pre-punched paper, Letterhead,  
Bond paper

PAPER DECK UNIT-E1:

Thin paper, Plain paper, Recycled paper, Colour  
paper, Heavy paper, Pre-punched paper, Letterhead,  
Bond paper

### Supported media sizes

Upper Left/Right Cassettes(1/2):  
Standard size: A4

Lower Cassettes (3/4):

Standard size: 330 mm x 483 mm, 320 mm x 450 mm  
(SRA3), 305 mm x 457 mm, A3, A4, A4R, A5R  
Custom size: 139.7 mm x 182 mm to 330.2 mm x 487.7 mm

Multi-purpose tray:

Standard size: 330 mm x 483 mm, 320 mm x 450 mm  
(SRA3), 305 mm x 457 mm, A3, A4, A4R, A5R  
Custom size: 100 mm x 148 mm to 330.2 mm x 487.7 mm  
Free size: 100 mm x 182 mm to 330.2 mm x 487.7 mm

POD DECK LITE-C1:

330 mm x 483 mm, 320 mm x 450 mm (SRA3),  
305 mm x 457 mm, A3, A4, A4R, A5R, and Custom Size  
(139.7 mm x 182 mm to 330.2 mm x 487.7 mm)

PAPER DECK UNIT-E1: A4

### Supported media weights

Cassettes: 52 to 220gsm  
Stack Bypass: 52 to 256gsm  
Duplex: 52 to 220 gsm

### Warm-up Time

From Power On: 60 Seconds or Less  
From Sleep Mode: 60 Seconds or Less  
Quick Startup Mode: 3 Seconds \*2

### Dimensions (W x D x H)

iR-ADV 8585/8595/8505: 1,481 mm x 770 mm x 1,252 mm

### Installation Space(W x D)

4,098 mm x 1,617 mm ( POD DECK LITE-C1 + BOOKLET  
FINISHER W1 + DOCUMENT INSERTION UNIT-N1 + PAPER  
HOLDING UNIT-J1 + BOOKLET TRIMMER-D1)

### Weight

iR-ADV 8585/8595/8505: Approx. 240kg \*3

## Print Specifications

### Printing method

Monochrome laser beam printing

### Print Speed

iR-ADV 8585	44 ppm (A3)
	85 ppm (A4)
	63 ppm (A4-R)
	85 ppm (A5R)
iR-ADV 8595	50 ppm (A3)
	95 ppm (A4)
	69.1 ppm (A4-R)
	95 ppm (A5R)
iR-ADV 8505	54 ppm (A3)
	105 ppm (A4)
	76.3 ppm (A4-R)
	105 ppm (A5R)

### Print Resolution

1,200 dpi x 1,200 dpi, 600 dpi x 600 dpi

### Page description languages

UFR II, PCL 5e/6 (Optional), Adobe PS 3 (Optional)

### Double Sided Printing

Automatic (Standard)

### Direct Print

Direct printing available from USB memory key,  
Advanced box, Remote UI and Web Access\*<sup>4</sup>  
\*Requires PS kit or Direct Print Kit.

### Printing from mobile and cloud

A range of software and MEAP-based solutions is  
available to provide printing from mobile devices or  
internet-connected devices and cloud-based services  
depending on your requirements. Please contact your  
sales representative for further information.

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T\* (Japanese, Korean,  
Simplified and Traditional Chinese)\*  
\*Requires optional PCL INTERNATIONAL FONT  
SET-A1.

PS fonts: 136 Roman

### Operating System

UFR II: Server 2003/Server 2003 R2/Vista/Server 2008/ Windows 7/  
Server 2008 R2/Windows 8/Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10, MAC OS X (10.5.8 or later)  
PCL: Server 2003/Server 2003 R2/Vista/Server 2008/ Windows 7/  
Server 2008 R2/Windows 8/Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10  
PS: Server 2003/Server 2003 R2/Vista/Server 2008/Windows 7/  
Server 2008 R2/Windows 8/Server 2012/Windows 8.1/  
Server 2012 R2/Windows 10, MAC OS X (10.5.8 or later)  
PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows  
Vista/Windows 7/Windows 8/Windows 8.1/Windows 10

## Copy Specifications (Available on the MFP version only)

### Copy Speed

iR-ADV 8585:	44 ppm (A3), 85 ppm (A4), 63 ppm (A4-R), 85 ppm (A5R)
iR-ADV 8595:	50 ppm (A3), 95 ppm (A4), 69.1 ppm (A4-R), 95 ppm (A5R)
iR-ADV 8505:	54 ppm (A3), 105 ppm (A4), 76.3 ppm (A4-R), 105 ppm (A5R)

### First-Copy-Out Time

iR-ADV 8505/8595/8585: Approx. 2.7 seconds or less

### Copy resolution

Reading: 600 dpi x 600 dpi  
Printing: 1,200 dpi x 1,200 dpi

### Multiple Copies

Up to 9,999 copies

### Magnification

25% - 400% (1% Increments)

### Pre-set Reductions

25%, 50%, 64%, 73%, 78%

### Pre-set Enlargements

121%, 129%, 200%, 400%

## Scan Specifications

### (Available on the MFP version only)

#### Standard

Colour flatbed scan unit and 300-sheet duplex automatic  
document feeder (1-Pass duplex colour scan).

#### Type

Colour flatbed plus Single-pass duplex automatic  
document feeder (1-Pass Duplex Scan)

#### Supported media size/s

A3, A4, A4R, A5, A5R

#### Supported media weight/s

Single-sided scanning: 38 to 220gsm (BW)  
Single-sided scanning: 64 to 220gsm (CL)  
Double-sided scanning: 50 to 220gsm (BW)  
Double-sided scanning: 64 to 220gsm (CL)

#### Pull Scan Spec

Colour Network ScanGear2. For both Twain and WIA  
Supported OS:  
Windows Vista/7/8/8.1/10  
Windows Server 2003/Server 2003 R2/Server 2008/Server  
2008 R2/Server 2012/Server 2012 R2

#### Scan Resolution

100 x 100dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi,  
200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

#### Acceptable Originals

Platen: Sheet, Book, 3-Dimensional Objects [Up to 2kg]  
Feeder size: A3, A4, A4R, A5, A5R  
Feeder weight  
Single-sided scanning: 38 to 220gsm (BW)  
Single-sided scanning: 64 to 220gsm (CL)  
Double-sided scanning: 50 to 220gsm (BW)  
Double-sided scanning: 64 to 220gsm (CL)

### Scan Method

Send functionality available on all models

Scan to USB Memory Key: Available on all models

Scan to Mobiles or internet-connected devices:

A range of solutions is available to provide scanning  
to mobile devices or internet-connected devices  
depending on your requirements. Please contact your  
sales representative for further information.

Scan to cloud-based services:

A range of solutions is available to provide scanning to  
cloud-based services depending on your requirements.  
Please contact your sales representative for further  
information.

TWAIN/WIA Pull scanning available on all models

### Scan Speed (BW/Colour; A4)

Single-sided (A4, 300 dpi): 120/120 ipm,  
Single-sided (A4, 600 dpi): 120/60 ipm (BW/CL);  
Double-sided (A4, 600 dpi): 120/60 ipm,  
Double-sided (A4, 300 dpi): 240/220 ipm (BW/CL)

### Paper Capacity

300 Sheets (80gsm)

### Double sided scanning

2-sided to 2-sided (Automatic)

### Universal Send Features

Original Type Selection, Two-sided Original, Book to  
Two Pages, Different-size Originals, Density Adjustment,  
Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's  
Name (TI), Select Line, Direct Send, Delayed Send,  
Preview, Finished Stamp, Job Done Notice, File Name,  
Subject/Message, Reply-to, E-mail Priority, TX Report,  
Original Content Orientation, Skip Blank Originals, Detect  
Feeder Multi Sheet Feed.

## Send Specifications

### Optional/ standard

Standard on MFP models

### Destination

E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV

### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

### Send resolution

100 x 100dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi,

200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

### Communication protocol

File: FTP, SMB, WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply  
policy, Optimize for Web, PDF A/1-b), XPS  
(Compact, Searchable), Office Open XML  
(PowerPoint, Word)

Optional: PDF (Trace&Smooth, Encrypted), PDF/XPS  
(Digital Signature)

## Fax Specifications

### Optional/ standard

Optional on all models

### Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution

400 x 400 dpi, 200 x 400 dpi,

200 x 200 dpi, 200 x 100 dpi

### Sending/Recording Size

A3, A4, A4R, A5 \*1, A5R \*2

\*1 Pels stands for picture elements (pixels)

\*2 Sent as A4

### FAX memory

Up to 6,000 pages

### Speed dials

Max. 200

### Group dials/destinations

Max. 199 dials

### Sequential broadcast

Max. 256 addresses

### Memory backup

Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages,  
Different-size Originals, Density for Scanning, Sharpness, Copy  
Ratio, Erase Frame, Job Build, Specifying the Sender's Name  
(when sending fax), Sender's Name (TI), Selecting the Telephone  
Line (when sending fax), Direct Send, Delayed Send, Preview,  
Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi  
Sheet Feed.

## Store Specifications

### Advanced Space Features:

Disabling Advanced Box, Storage Filtering, Authentication for  
Advanced Box Log-in, Search Function, Sort Function, Printing a  
PDF File with a Password, imageWARE Secure Audit Manager  
Support

### Memory Media

Standard: USB Memory

## Store Specifications

### Authentication

Standard: Universal Login Manager, User Authentication,  
DepartmentID Authentication, (Device and Function  
Level Log-in), Access Management System

### Optional:

My Print Anywhere secure print (Requires uniFLOW)

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password  
Lock, Hard Disk Drive Erase, Mail Box Password  
Protection, Hard Disk Drive Encryption(FIPS 140-2  
Validated)

Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal,  
IEEE 2600.2 Common Criteria Certification, Data Loss  
Prevention (Requires uniFLOW)

**Network**

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

**Document**

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF

Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

**Environment Specifications****Operating Environment**

Temperature: 10 to 30 °C (50 to 86 °F)  
Humidity: 20 to 80 % RH (no condensation)

**Power source**

220-240V (±10 %), 50/60Hz (±2 Hz), 10Amp

**Power consumption**

Maximum: Approx. 2.4 kW  
Standby: Approx. 222 W  
Energy Saver Mode: Approx. 193 W  
Sleep mode: Approx. 0.9 W or less\*5  
Typical Electricity Consumption (TEC) rating<sup>2</sup>  
9.1 kWh (IR-ADV 8585)  
10.9 kWh (IR-ADV 8595)  
10.7 kWh (IR-ADV 8505)

**Consumables**

**Toner Cartridge/s**  
NPG-53 TONER BK

**Toner (Estimated Yield @6% Coverage)**  
70,000 pages

**Footnotes****Supported media types**

<sup>1</sup> Some types of tracing paper cannot be used.

**Warm-up Time**

<sup>2</sup> The time until key operations can be performed on the touch panel display is 3 seconds or less.

**Weight**

<sup>3</sup> Including the toner bottle.

**Direct Printing from memory media**

<sup>4</sup> PDF print from websites is supported.

**Power consumption**

<sup>5</sup> 0.9 watt sleep mode may not be possible in all circumstances.

# Canon

Delighting You Always

**SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #15-01 Galaxis Singapore 138522

Tel: 65-6799 8888 | Fax: 65-799-8882 | [www.canon-asia.com](http://www.canon-asia.com) | [www.canon.com.sg](http://www.canon.com.sg)

**CANON OFFICES****MALAYSIA**

Canon Marketing (Malaysia) Sdn Bhd  
Block D, Peremba Square  
Saujana Resort Section U2,  
40150 Shah Alam  
Selangor Darul Ehsan, Malaysia  
Tel : 60-3-7844 6200 /  
7845 0055  
Fax : 60-3-7844 6196 / 6198  
[www.canon.com.my](http://www.canon.com.my)

**THAILAND**

Canon Marketing (Thailand) Co. Ltd  
No.98 Sathorn Square  
Office Tower, 22nd - 24th  
floor, North Sathorn Road,  
Silom, Bangkok,  
Bangkok 10500  
Tel : 66-2-344 9999  
Fax : 66-2-344 9960  
[www.canon.co.th](http://www.canon.co.th)

**VIETNAM**

Canon Marketing (Vietnam) Co. Ltd  
Level 10, President Place,  
93 Nguyen Du, Dist 1,  
Ho Chi Minh City,  
Vietnam  
Tel : 84-8-3820 0466  
Fax : 84-8-3820 0477  
[www.canon.com.vn](http://www.canon.com.vn)

**INDIA**

Canon India Private Limited  
7th Floor, Tower B, Building #5,  
DLF Epitome, DLF Phase III,  
Gurgaon 122002,  
Haryana, India  
Tel : 91-124-416 0000  
Fax : 91-124-416 0011  
[www.canon.co.in](http://www.canon.co.in)

**HONG KONG**

Canon Hongkong Co. Ltd  
19F, The Metropolis Tower  
10 Metropolis Drive  
Hung Hom, Hong Kong  
Tel : 852-3191-2388  
Fax : 852-2369-3800  
[www.canon.com.hk](http://www.canon.com.hk)

**TAIWAN**

Canon Marketing (Taiwan) Co. Ltd  
19F, No. 100,  
Sec.2 Roosevelt Road,  
Taipei, Taiwan, R.O.C.  
Tel : +886 2-6632-8888  
Fax : +886-2-6632-6700  
[www.canon.com.tw](http://www.canon.com.tw)

**PHILIPPINES**

Canon Marketing (Philippines), Inc.  
7F Commerce and Industry  
Plaza, 1030 Campus Avenue  
Corner Park Avenue,  
McKinley Hill, Fort Bonifacio,  
Taguig City, Metro Manila,  
Philippines 1634  
Tel : 632-884-9000  
Fax : 632-556-1456  
[www.canon.com.ph](http://www.canon.com.ph)

**CANON BUSINESS PARTNERS****AFGHANISTAN**

Megaplus Afghanistan Limited  
House No. 233, Street No. 4,  
Charagh Ali,  
Qilla-e-Fatehullah,  
Kabul, Afghanistan  
Tel : 93-700 228 832 /  
93-700 979 5  
Fax : 93-202 201 259  
Email: [info@megaplus.com.af](mailto:info@megaplus.com.af)

**BANGLADESH**

Flora Limited  
Adamjee Court Annex-2  
(4th Floor)  
119-120 Molljheel  
Commercial Area  
Dhaka 1000 Bangladesh  
Tel : 880-2-716-2742-46 / 225  
Fax : 880-2-955-0030  
[www.floralimited.com](http://www.floralimited.com)

**BRUNEI**

Inferhouse Company  
No. 5-7 Bunut Jaya Complex  
Spg 574 Jalan Tutong BF1320  
P.O. Box 423, Seri Complex  
Bandar Seri Begawan  
BA 1779 Brunei Darussalam  
Tel : 673-2-653-001  
Fax : 673-2-653-003

**CAMBODIA**

Royal Cambodia Co., Ltd  
#437 Preah Monivong Blvd  
Phnom Penh  
Kingdom of Cambodia  
Tel : 855-23-428955  
Fax : 855-23-722961

**INDONESIA**

PT Samafitro  
Jalan Ir. H Juanda No.8  
Jakarta 10120, Indonesia  
Tel : 62-21-345 8989  
Fax : 62-21-345 6699  
[www.samafitro.co.id](http://www.samafitro.co.id)

**MALDIVES**

Simdi Company Pvt Ltd.  
G.Manaam Building,  
2/1 Neeloafaru Magu,  
Male\* 20-129, Maldives  
Tel : 960-333 4421  
Fax : 960-333 4424

**MYANMAR**

Myanmar Golden Rock  
International Co., Ltd  
No. 79-D, Bo Chein Street,  
Pyay Road, 6 1/2 Mile,  
Hlaing Township,  
Yangon, Myanmar  
Tel : 95-1-654810 to 19  
(10 Lines),  
95-1-654844 to 48  
(5 Lines)  
Fax : 95-1-654820  
Email: [sales@mgr.com.mm](mailto:sales@mgr.com.mm)

**NEPAL**

International Electronics  
Concern (P) Ltd  
Kha 14, 1st Floor  
Haratibhawan Putalisadak  
Ramshah Path,  
Kathmandu, Nepal  
P.O. Box 12588  
Tel : 977-1-442 1991  
Fax : 977-1-442 1909

**PAKISTAN**

Shirazi Trading Company  
(Pvt.) Ltd  
8th Floor, Adamjee House  
I.I. Chundrigar Road  
Karachi 74000 Pakistan  
Tel : 92-21-3241 (7659),  
(7737) or (7746),  
Tel : 92-21-(3241 7747),  
(3242 0417) or  
(3242 0418)  
[www.shirazitrading.com.pk](http://www.shirazitrading.com.pk)

**SRI LANKA**

Metropolitan Office (Pvt) Ltd  
12, Magazine Road  
Colombo 08  
Sri Lanka  
Tel : 94-11-470 0200  
Fax : 94-11-470 0267  
[www.metropolitan.lk](http://www.metropolitan.lk)

This brochure and the specifications of the product have been developed prior to the date of product launch. These specifications are subject to change without notice. Therefore no representations or warranties, either express or implied, are made of the fitness of this product for a particular purpose. In no circumstances shall the information in this brochure be considered part of our terms and conditions of sale. You are advised to check the prevailing specification immediately prior to purchase.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners.

0201W095 © 2016 Canon Singapore Pte. Ltd.  
All rights reserved. Printed in Singapore.