

Specifications for imageRUNNER ADVANCE C9065 PRO

Type	Console	
Maximum Original Size	A3	
Copy Sizes	Cassette1.2:	A4
	Cassette3.4:	A5R-SRA3 (320 x 450mm), (330 x 483mm)
	Stack Bypass:	A5R-SRA3 (320 x 450mm), (330 x 483mm) Custom Size, 100 x 148mm to 330.2 x 487.7mm Optional Envelope Feeder, COM10 No.10, Monarch, DL, ISO-B5, ISO-C5
Resolution	Reading:	600 x 600dpi
	Copying:	600 x 600dpi
	Printing:	1200 x 1200dpi (text / line only) 256 Gradations
Copy / Print Speed	A4 (80gsm):	65ppm (BW / Colour)
Magnification	Zoom:	25 - 400%
First Copy Time	BW:	4.9secs.
	Full Colour:	6.6secs.
Warm-Up Time	5 minutes	
Multiple Copies / Prints	1 to 9999 sheets	
Paper Weight	Cassette:	52 to 220gsm
	Stack Bypass:	52 to 300gsm
	Duplex:	52 to 220gsm
Paper Capacity	Standard:	1,100 sheets x 2 cassettes (80gsm) 550 sheets x 2 cassettes (80gsm) Stack Bypass: 100 sheets (80gsm)
	Paper Deck:	3,500 sheets, Multi-drawer Paper deck: 6,000 sheets
	Total Capacity:	6,900 sheets, Multi-drawer Paper deck: 9,400 sheets
CPU	Canon Custom Processor, 1.2GHz	
Memory	Standard:	2GB RAM
	Maximum:	2.5GB RAM
Hard Disk Drive	Standard:	80GB (Available Disk Space: 10GB)
	Maximum:	1TB (Available Disk Space: 675GB)
Interface	Ethernet (1000BaseT / 100Base-TX / 10Base-T) Wireless LAN (IEEE802.11b/g, Optional), USB2.0	
Power Supply	220 - 240V AC, 50 / 60Hz	
Power Consumption	3kW max.	
Dimensions (W x D x H)	1180 x 932 x 1403mm (with Optional 1PDS & Standard Upright Control panel)	
Weight (approx.)	288kg (with Optional 1PDS & Standard Upright Control Panel) 282kg (with Optional 1PDS)	

Print Specification		
PDL		UFR II (Standard), PCL 5c / 6 (Optional), Adobe PostScript 3 (Optional)
Resolution		1200 x 1200dpi (text / line only), 600 x 600dpi
Memory		2GB (Uses Main unit RAM)
Hard Disk	Standard:	80GB (Available Disk Space: 10GB)
	Maximum:	1TB (Available Disk Space: 675GB)
CPU		Canon Custom Processor, 1.2GHz (Uses Main unit CPU)
PS Fonts		Roman 136
PCL Fonts		Roman 93, Bitmap10, OCR2
Supported OS	PCL:	Windows2000 / XP / Server2003 / Vista / Server2008 / Win7
	Adobe PostScript 3:	Windows2000 / XP / Server2003 / Vista / Server2008 / Win7, Mac OSX (10.4.9 or later)
UFR II	Windows:	2000 / XP / Server2003 / Vista / Server2008 / Win7
	Mac:	OSX (10.4.9 or later)
Mac-PPD		Mac OS 9.1 or later, Mac OSX (10.2.8 or later)
Interface		Ethernet (1000Base-T / 100Base-TX / 10Base-T) Wireless LAN (IEEE802.11b/g, Optional), USB2.0
Network Protocol		TCP / IP (LPD / Port9100 / WSD / IPP / IPPS / SMB / FTP), IPv6, IPX / SPX (NDS, Bindery), AppleTalk
Pull Scan		Network TWAIN Driver (75 to 600dpi 24bit colour / 8 bit grayscale / 2 bit BW)
Send Specification (Standard)		
Scan Speed		(A4, 300dpi) 120ipm (Colour / BW), 200ipm (BW) / 140ipm (Colour) with optional 1PDS
Scan Resolution		100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi
Destinations		E-Mail / Internet FAX (SMTP), PC (SMB, FTP), iWDM, WebDAV
Address Book		LDAP, Local (Max.1800)
File Format		TIFF, JPEG, PDF, XPS, High compression PDF / XPS, PDF / A-1b, Optimize PDF for Web