Epson **FX-2190**

No.1 WORLD LEADER
IMPACT DOT MATRIX PRINTER
SINCE 1996

At a class-leading 680 cps up to A3 size, this 9-pin printer handles medium to large volume printing quicker than ever.

This wide carriage printer combines high speed printing with outstanding reliability.

A mean volume between failure of 52 million lines makes this printer suitable for medium and large print volumes. The paper can be fed from the front, top, rear or bottom and an optional additional push/pull tractor unit can store a second continuous form, which is ideal for commercial and industrial environments. Also available as network version FX-2190N.

KEY FEATURES

- Class-leading speed - up to 680cps
- Compact, robust and reliable
- Long-lasting ribbon
- Flexible paper handling from front, top, rear and bottom
- Handles media up to 136 columns wide

EPSON®
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins	9 pins
Number of columns	136 columns

PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 566 chars/s, 12 cpi: 680 chars/s, Draft: 10 cpi: 419 chars/s, NLQ: 10 cpi: 104 chars/s
Carbon Copies	6 plus one original
Printing Resolution	240 x 144 dpi

CONNECTIVITY

Interfaces	Bidirectional parallel, Ethernet interface (100 Base-TX / 10 Base-T) (optional), USB 2.0 Type B, RS-232 (optional), Type B interface

PAPER / MEDIA HANDLING

Document Feed	Single sheet front and rear, Continuous paper front and rear, Paper output rear, Optional Automatic Document Feed (CSF): 150
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes, Cardboard

GENERAL

Energy Use	53 W, 45 W (standby)
Energy Star	Yes
Product dimensions	589 x 350 x 168 mm (Width x Depth x Height)
Product weight	9.4 kg
Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	20,000 Hours
Print Head Life	400 Million Strokes/Wire
Sound Pressure	Operation: 55 dB (A)
Memory	128 kB included
Ribbon Yield	12000000 characters Black Draft

OTHER FEATURES

Emulations	ESC/P, IBM PPDS, IBM PPDS/ML

OTHER

Warranty	12 months Carry in
	Optional warranty extension available

LOGISTICS INFORMATION

SKU	C11C526022
	C11C526023
EAN code	8715946333151
Dimensions Single Carton	460 x 700 x 270 mm
Carton Weight	9 Kg
Country of Origin	Indonesia
Layer	2 Units

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Power cable
- Ribbon

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for FX-2190 (C13S015327) (C13S015327)
- Epson SIDM Black Ribbon Cartridge for FX-2190 (C13S015327BA) (C13S015327BA)

OPTIONAL ACCESSORIES

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series
  C12C811141
- Epson SIDM Serial I/F board, no buffer type-B plug-in card RS232D/20mA
  C12C824432
- Epson SIDM Push/pull tractor unit for FX-2190, LQ-2090
  C12C800212
- Epson SIDM Single Sheet Feeder 50 sheets for LQ-2090, LX-1170II, FX-1180/2190
  C12C806392
- Epson SIDM Front Sheet Guide for FX-2190, LQ-2090
  C12C814011
- Epson SIDM Type B EpsonNet 10/100 Base Tx Internal Print Server 5
  C12C824352

EPSON®