Epson **FX-890**

WORLD LEADER
IMPACT DOT MATRIX PRINTER
SINCE 1996

At a class-leading 680 characters per second, this 9-pin printer will handle all your medium to large volume printing quicker than ever.

The new Epson FX-890 dot matrix printer is built to offer faster printing, better reliability and flexible paper handling, in a stylish and compact design. It is perfect for production, car dealers, warehouses, labs, wholesalers, freight forwarders, finance departments and trade users who want high performance at low cost.

FX-890 dot matrix printer, 18 pins, 80 column, original + 6 copies(pull tractor), 566 cps UHSD (10 cpi), ESC/P, IBM PPDS , 16 fonts, 8 BarCode fonts, single sheet and continuous, 4 paper paths, paper park, USB and Parallel I/F, 1 slot for opt. Epson Type B I/F card.

KEY FEATURES

- Class-leading speed - up to 680cps
- Compact, robust and reliable
- Long-lasting ribbon
- Handles 1 original + 5 copies
- Flexible paper handling from front, top, rear and bottom

EPSON®
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins	9 pins
Number of columns	80 columns

PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 566 chars/s, 12 cpi: 680 chars/s, Draft: 10 cpi: 419 chars/s, NLQ: 10 cpi: 104 chars/s, 12 cpi: 125 chars/s
Carbon Copies	6 plus one original
Character Tables	PC437, PC708, PC720, PC850, PC858, PC864, ISO-8859-15, Roman 8

CONNECTIVITY

Interfaces	Bidirectional parallel, Ethernet interface (100 Base-TX / 10 Base-T) (optional), USB 2.0 Type B, RS-232 (optional), Type B interface

PAPER / MEDIA HANDLING

Document Feed	Single sheet front and rear, Continuous paper front and rear, Paper output rear, Optional Automatic Document Feed (CSF): 150
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes, Cardboard

GENERAL

Energy Use	53 W, 3.4 W (standby)
Energy Star	No
Product dimensions	414 x 350 x 168 mm (Width x Depth x Height)
Product weight	7.2 kg
Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows 98, Windows Vista, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	20,000 Hours
Print Head Life	400 Million Strokes/Wire
Sound Pressure	Operation: 55 dB (A)
Memory	128 kB included
Ribbon Yield	7500000 characters Black Draft

OTHER FEATURES

Emulations	IBM PPDS, ESC/P

OTHER

Warranty	12 months Carry in
	Optional warranty extension available

LOGISTICS INFORMATION

SKU	C11C524025
	C11C524026
EAN code	8715946333137
Dimensions Single Carton	465 x 530 x 270 mm
Carton Weight	8.6 Kg
Country of Origin	Indonesia
Layer	2 Units

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for FX-890, FX-890A (C13S015329) (C13S015329)
- Epson SIDM Black Ribbon Cartridge for FX-890 (C13S015329BA) (C13S015329BA)

OPTIONAL ACCESSORIES

- Epson SIDM Type B EpsonNet 10/100 Base Tx Internal Print Server 5
  C12C824352
- Epson SIDM Push/Pull Tractor Unit for LQ-590/870, FX-890/A
  C12C800202
- Epson SIDM Single Sheet Feeder 50 sheets for FX-890/A, LX/LQ-300+II, LQ-590
  C12C806372
- Epson SIDM Single Sheet Feeder 150 sheets for LQ-590, FX-890/A
  C12C806382
- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series
  C12C811141
- Epson SIDM Serial I/F board, no buffer type-B plug-in card RS232D/20mA
  C12C824432
- Epson SIDM Front Sheet Guide for FX-890, LQ-590
  C12C814022

EPSON®