## **AF-P DX NIKKOR 10-20mm f/4.5-5.6G VR**



Focal Length Range: 10 -20 mm

Maximum Aperture: f/ 4.5-5.6

Format: DX

VR (Vibration Reduction) Image Stabilization: Yes Lens shift using voice coil motors (VCMs)

Approx. Dimensions (Diameter x Length): 3.0 in. (77 mm) x 2.8 in. (73 mm) Distance from camera lens

mount flange

Approx. Weight: 8.2 oz. (230 g)

**Mount Type: Nikon F-Bayonet** 

Focal Length Range: 10 -20 mm

Zoom Ratio: 2 x

Maximum Aperture: f/ 4.5-5.6

Minimum Aperture: f/ 29

Format: DX

Maximum Angle of View (DX-format):109°

Minimum Angle of View (DX-format):70°

**Maximum Reproduction Ratio: 0.17 x** 

**Lens Elements: 14** 

**Lens Groups: 11** 

**Optical Conversion Factor: 1.5x** 

**Compatible Format(s)** :DX

VR (Vibration Reduction) Image Stabilization: Yes Lens shift using voice coil motors (VCMs)

**Diaphragm Blades: 7** 

**Aspherical Elements: 3** 

**Super Integrated Coating: Yes** 

**Autofocus: Yes** 

**AF-P** (Pulse Motor) : Yes

**Internal Focusing: Yes** 

**Minimum Focus Distance:** 0.8 ft. (0.22 m) from focal plane at all zoom positions

Focus Mode: Auto, Manual, Manual/Auto

G-type: Yes

Filter Size: 72 mm

**Accepts Filter Type: Screw-on** 

Approx. Dimensions (Diameter x Length): 3.0 in. (77 mm) x 2.8 in. (73 mm) Distance from camera lens

mount flange. Based on CIPA Guidelines

Approx. Weight: 8.2 oz. (230 g)Based on CIPA Guidelines